

PYROTEX EXTREME **coated jacket fire hose**

Jacket:

- 100% high tenacity synthetic yarn circular woven
- 2-ply warp threads or 3-ply warp threads

Lining:

- EPDM - rubber compound
- low friction loss
- ageing and ozon resistant, resistance to chemicals and sea water

External coating:

- synthetic coating
- very good abrasive resistance
- better resistance to oil and chemicals

Applications:

- municipal and industrial fire brigades
- ships
- refineries
- military

Temperature:

- can be used at temperatures ranging from -30°C till + 80°C

Approvals:

- M.E.D.

Standard colour:

red, signal yellow

Standard lengths:

15,20,25,30,40m (others on request)



Technical parametres

inner diameter (mm)	weight (g/m)*	working pressure (Mpa)*	test pressure (Mpa)	burst pressure (Mpa)
2F 25	136	1,6	2,4	6
2F 38	210	1,6	2,4	6
2F 42	230	1,6	2,4	6
2F 45	247	1,6	2,4	6
2F 52	300	1,6	2,4	6
2F 64	348	1,6	2,4	6

2F 65	355	1,6	2,4	6
2F 70	401	1,6	2,4	6
2F 75	461	1,6	2,4	6
3F 38	236	1,6	2,4	6
3F 42	264	1,6	2,4	6
3F 52	327	1,6	2,4	6
3F 75	471	1,6	2,4	6

** Data applies to hose without couplings*

Other sizes on request