

## TECHMATEX FIRE rubber covered fire hose

### Jacket:

- 100% high tenacity polyester and polyamide circulat woven
- jacket is embedded in rubber lining and cover

### Lining and cover:

- NBR/PVC compound
- through the weave extrusion process
- minimum friction loss
- very good resistance to oil and chemicals
- very good ageing and UV resistance
- ribs on the surface for high abrasion resistance

### Applications:

- municipal and industrial fire brigades
- ships
- refineries
- industrial use
- military

### Temperature:

can be used at temperatures ranging from -30°C to + 80°C

### Standard colour:

red, yellow

### Standard lengths:

15,20,25,30,40m (others on request)

### Approvals:

- Russian maritime register of shipping
- M.E.D.



### Technical parametres

inner diameter (mm)	weight (g/m)*	working pressure (Mpa)*	test pressure (Mpa)	burst pressure (Mpa)
AIR 19	200	1,6	2,4	6
AIR 25	234	1,6	2,4	6
38	321	1,6	2,4	5
40	326	1,6	2,4	5
45	407	1,6	2,4	5

52	460	1,6	2,4	5
55	481	1,6	2,4	5
64/65	570	1,6	2,4	5
70	701	1,6	2,4	5
75	761	1,6	2,4	5
102	1220	1,2	1,8	4
127	1816	1,2	1,8	3,5

*\* Data applies to hose without couplings*

**Other sizes on request**